

## DEPENDENT RESURVEY OF THE EAST BDY. OF T. 17 N., R. 19 E.

Chains

of stone, 5 ft. base, 8 ins. high, around post.

Land, broken mountainous.

Soil, shallow coarse rocky clay loam, 3rd rate.

Undergrowth, sagebrush, buckbrush, willows, chokecherry, wild peach.

Timber, aspen and cottonwood along creek bottom; isolated clumps of mountain mahogany on higher slopes.

Grazing, good.

N. 0° 03' E., bet. secs. 1 and 6, (South half mile.)


Asc. 370 ft. over broken, rocky SE. to E. slopes thru medium dense low undergrowth.

35.10 Top of ascent and minor divide, slopes NE. from W., desc. 50 ft. over broken, rocky N. slope.

39.80 The original  $\frac{1}{4}$  sec. cor. of secs. 1 and 6 which is a basalt rock, 28x10x5 ins., mkd.  $\frac{1}{4}$  on W. face, loosely set in a mound of stone on rocky NE. slope in a mass of basaltic outcrops.

At point for cor., in center of mound,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the original stone deposited at the base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



raise a circular mound of stones, 5 ft. diam., 8 ins. high, around post.

Thence

N. 0° 10' E., bet. secs. 1 and 6, (North half mile.)

Desc. 180 ft. over broken NE. slope gradually changing to N. slope.

9.90 Old mine road, bears W. and E. 30 chs. to old mine workings.

Desc. 140 ft. over steep N. slope.


18.70 Head of draw, drains NE., desc. along E. side of rocky spur.

31.30 Flat rocky spur, slopes NE., desc. 50 ft. over rocky N. slope.

40.00 The original cor. of Tps. 17 and 18 N., Rs. 19 and 20 E. is a basalt rock, 22x14x12 ins., mkd. with 6 notches on each edge, firmly set in an old embedded mound of stone.

At point for cor., in center of mound,

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to solid rock, with the original stone deposited at the base, and in a large mound of stone to top, for the cor. of Tps. 17 and 18 N., Rs. 19 and 20 E., with brass cap mkd.



1943

from which,