

Dependent Resurvey, South Boundary, T. 17 N., R. 19 E.

Chains

- 76.05 Unimproved road, bears SW. to Washoe Lake and N. 10° E.
- 80.00 The cor. of Ts. 16 and 17 N., Rs. 19 and 20 E., monumented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record of the Dependent Resurvey of T. 17 N., R. 19 E., executed under Group 332, Nevada.
- Land, west 3/4 mile, marshy; balance, nearly level sandy plain. Soil, silt loam to fine sandy loam. Undergrowth, tules and rushes for west 3/4 mile; balance, rabbit brush, yellow top and sagebrush. No timber.

Dependent Resurvey, West Boundary, T. 17 N., R. 19 E.

Reestablishment of the Survey Executed by
Porter C. Rector, Deputy Surveyor, in 1865, under Contract No. "G".

From the cor. of Ts. 16 and 17 N., Rs. 18 and 19 E.

N. 0° 23' E., bet. secs. 31 and 36.

Over rough mountainous land, through medium heavy timber and dense undergrowth; asc. and desc. along broken W. slope.

- 7.20 Head of draw, drains W.; asc. 250 ft. over very rocky SW. slope.
- 22.60 Crest of divide, bears E. and W.; desc. 435 ft. over abrupt rocky and broken N. slope to the $\frac{1}{4}$ sec. cor.
- 39.64 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, marked by an unmarked granite stone, 22x8x5 ins., firmly set in center of an old embedded mound of stone, with a surfaced stake alongside, mkd. $\frac{1}{4}$ S.
- At the corner point, in center of the old mound,
- Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 36 | S 31
1945

from which

A tamarack, 18 ins. diam., bears N. 81 $\frac{1}{2}$ ° E., 69 lks. dist., mkd. $\frac{1}{4}$ S31 BT.

A limber pine, 24 ins. diam., bears S. 58 3/4° W., 19 lks. dist., mkd. $\frac{1}{4}$ S36 BT.

Bury the old stone at base of the iron post.

N. 0° 16' W., beginning new measurement.

Desc. gentle NE. slope.

- 2.70 Head of small drain, course NE.
- 3.80 End of low spur from the SW.; desc. 100 ft. over N. slope.