

Subdivision of T. 33 N., R. 70 E.

Chains.

- 42.00 Wash, course S. 10° W.; asc. 92 ft. over the SW. slope of a small isolated peak.
- 47.60 Top of ascent on precipitous S. edge of peak bearing N. and S.; desc. 96 ft. over SE. talus slope.
- 51.50 Vertical W. bank of large gravel pit, 12 ft. high, bears N. and S.; thence across bottom of pit,
- 52.96 Intersect the Nevada-Utah state line.
- Point for the closing corner of secs. 10 and 15
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

NEVADA	CC	T 33 N S 10 S 15 R 70 E	UTAH
1947			

from which

The NE. corner of a corrugated iron house bears S. 24° 35' W., 1.30 chs. dist.

An aircraft beacon light bears N. 68° 34' W., about 4 chs. dist. on top of peak.

An aircraft beacon light bears N. 33° 03' W., about 28 chs. dist.

Raise a flat mound of stone, 5 ft. base, around post.

From this point mile post No. 41 on the Nevada-Utah state line bears S. 0° 39' W., 29.27 chs. dist.

Land, foothills.
Soil, sandy to exposed bedrock.
Undergrowth, shadscale.

The point for the E. $\frac{1}{4}$ sec. cor. of sec. 15 is at mid-point, and on the Nevada-Utah state line.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.

$\frac{1}{4}$ S 15
1947

From this corner mile post No. 41 on the Nevada-Utah state line bears N. 0° 18' E., 10.73 chs. dist.