

Dependent Resurvey of the Subdivision of T. 21 S., R. 62 E.


Chains

39.30 Wash, 100 lks. wide, drains NW.

39.80 The orig. $\frac{1}{4}$ sec. cor., a limestone, 10x10x9 ins., loosely set, mkd. $\frac{1}{4}$ on W. face.

At the cor. point, with the orig. cor. stone deposited at base, in wash, drains N. 60° W.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

From the cor., I take the following bearings to the improvements of Frenchman Mine:

Portal of tunnel bears N. 81° 48' E.

NW. cor. of foundation of building bears N. 89° 59' E.

NW. cor. of concrete building bears S. 76° 18' E.

Thence

N. 0° 53' E., beginning new measurement.


3.90 Graded road, bears N. 60° W. and S. 60° E. to Frenchman Mine.

20.70 Wash, 30 lks. wide, drains NW.

40.26 The orig. closing cor. of secs. 1 and 2, on the 5th Stan. Par. S., a limestone, 14x10x8 ins., loosely set, mkd. with 5 grooves on W. face and 1 groove on E. face.

At the cor. point, with the orig. cor. monument deposited at base,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 1 and 2, with brass cap mkd.



raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From the cor., the stan. cor. of secs. 35 and 36, bears S. 89° 04' E., 12.97 chs. dist.

Land, broken and mountainous.
Soil, sandy, mixed with gypsum, with strata of gravel; 4th rate.
Timber, a few scattered mesquite.
Undergrowth, chaparral and other desert brush.
Poor grazing land.