

440

Dependent Resurvey of the Subdivision of T. 21 S., R. 62 E.

Chains

$$\frac{1}{4} \frac{S 4}{S 9}$$

1943

deposit glass at
base of post, and raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft.
high, N. of cor.

Thence

S. $88^{\circ} 19'$ W., beginning new measurement.

Continue over level land.

40.24

The cor. of secs. 4, 5, 8, and 9.

Land, nearly level.

Soil, fine silt and blow sand, 3d rate.

No timber.

Undergrowth, shadscale, sagebrush, and mesquite.

Poor grazing land.

N. $0^{\circ} 06'$ W., bet. secs. 4 and 5.

Over rolling valley, through short undergrowth.

35.00

Enter area of mesquite, bears N. 60° W. and SE.

35.80

Dim road at N. edge of area of mesquite, bears NW. and SE.

41.81

Proportionate point, on E. side of road bearing N. and S.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground,
for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4}$$

$$S 5 | S 4$$

1943

raise a mound
of stone, 3 ft. base, 2 ft. high, E. of cor. (mound
erected to E. of cor. monument on account of road.)

42.20

Old road, bears W. and S. 70° E.

52.55

Shallow wash, 5 lks. wide, drains SE.

53.70

Unimproved road, bears E. and W.

80.49

Intersect a rotted pine post, 4 ft. long, 4 ins. square.

80.99

The point for the closing cor. of secs. 4 and 5, mkd. by a concrete
post, 18 ins. long, 6 ins. diam., firmly set, with a copper nail
in top of same.

At the point for cor., with the concrete post deposited alongside,
at E. edge of intersection of road from S., with Charleston road
bearing E. and W.,

Set an iron post, 3 ft. long, 2 ins. diam., 54 ins. in the ground,
for closing cor. of secs. 4 and 5, with brass cap mkd.

$$T 20 S R 62 E$$

$$\frac{S 32}{S 5 | S 4}$$

$$T 21 S | R 62 E$$

C C
1943