

466

Dependent Resurvey of the East Boundary of T. 22 S., R. 61 E.

Chains	
	Reestablishment of the survey executed by Hunt and Proctor, Deputy Surveyors, in 1881.
	<hr/>
	<p>From the cor. of Tps. 22 and 23 S., Rs. 61 and 62 E. N. 0° 58' E., bet. secs. 31 and 36.</p> <p>Over rolling and broken land, through medium dense undergrowth; slight descent over general NW. exposure.</p>
1.60	Wash, 10 lks. wide, 3 ft. deep, drains NW.; ascend 40 ft.
8.00	S. edge of table land, bears N. 30° W. and SE.
18.00	N. edge of same, bears N. 30° W. and S. 30° E.; descend 50 ft.
28.25	Shallow wash, drains N. 20° W.
40.09	The original $\frac{1}{4}$ sec. cor., a lava stone, 12x12x10 ins., mkd. $\frac{1}{4}$ on W. face and set in a small mound of stone.
	<p>At cor. point, with the old corner stone deposited at the base,</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p>
	<p>S 36 S 31</p> <p>1942</p>
	<p>raise a mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, W. of cor.</p>
	<p>Thence</p> <p>N. 0° 41' W., beginning new measurement.</p>
20.00	Low spur, slopes NW.
40.12	The original cor. of secs. 25, 30, 31, and 36, a lava stone, 12x8x8 ins., mkd. with 1 groove on S. face and 5 grooves on N. face, firmly set in a small mound of stone.
	<p>At cor. point, with the old corner stone deposited at the base,</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to bedrock, supported in a mound of stone to top, for cor. of secs. 25, 30, 31, and 36, with brass cap mkd.</p>
	<p>T 22 S</p> <p>R 61 E R 62 E</p> <p>S 25 S 30</p> <p>S 36 S 31</p> <p>1942</p>
	<p>Land, rolling, general NW. slopes and drainage.</p> <p>Soil, volcanic ash, gravelly and rocky, 4th rate.</p> <p>Undergrowth, creosote, cacti, and some greasewood.</p> <p>Grazing, poor.</p>
	<p>N. 0° 50' E., bet. secs. 25 and 30.</p> <p>Over rolling land, through short undergrowth.</p>
24.00	Small wash, drains NW.

Begin