

522

## Dependent Resurvey of a Portion of the East Boundary of T. 21 S., R. 63 E.

Chains

T 20 S R 63 E  
 S 36  
 T 21 S  
 R 63 E  
 S 1  
 C C  
 1943

deposit a sandstone,  
 1 1/2 x 1 0 x 2 ins., mkd. with a cross (+), at base of post.

Land, rolling and nearly level, with general southeasterly exposure and drainage.

Soil, gravelly and rocky; 4th rate.

Undergrowth, creosote.

Grazing, poor.

## Dependent Resurvey of the Subdivision of T. 21 S., R. 63 E.

Reestablishment of surveys executed by T. A. Magee,  
 Deputy Surveyor, in 1883.

From the cor. of secs. 35 and 36, on the S. bdy. of the Tp., an iron post, 2 ins. diam., set, mkd., and witnessed as described in the official record of the resurvey of T. 22 S., R. 63 E.

N. 1° 05' W., bet. secs. 35 and 36.

Over mountainous land, through scattered undergrowth; descend gradually.

11.00 Wash, drains NW.; ascend 50 ft. along W. slope.

19.00 Top of ascent on W. slope; descend 170 ft. over NW. slope.

33.00 Wash, drains N. 5° W. from S. 10° W.; ascend gradual, broken W. slope.

40.53 Proportionate point, on E. bank of wash, drains N. 10° W.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

↑  
 S 35 | S 36  
 1943

raise a mound  
 of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

68.00 Spur, 170 ft. above cor., slopes N. 20° W.; descend gradually.

76.20 Cable telephone line, bears N. 44° 30' E. and S. 44° 30' W.; service road along telephone line.

81.06 Proportionate point.

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to rock, and in a mound of stone, for the cor. of secs. 25, 26, 35, and 36, with brass cap mkd.

T 21 S R 63 E  
 S 26 | S 25  
 S 35 | S 36  
 1943