

530

Dependent Resurvey of the Subdivision of T. 21 S., R. 63 E.

Chains

- 72.00 Wash, 4.00 chs. wide, drains S. 70° E.; ascend 20 ft.
- 79.15 Intersect the Fifth Standard Parallel South, on the S. bdy. of sec. 35, T. 20 S., R. 63 E., West 16.25 chs. (record distance) from the stan. cor. of secs. 35 and 36, an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.
- At point of intersection
- Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 1 and 2, with brass cap mkd.
- T 20 S R 63 E
S 35

S 2 | S 1
T 21 S | R 63 E
C C
1943
- raise a mound
- of stone, 2 ft. base, 1½ ft. high, S. of cor.
- Land, rolling and hilly.
Soil, gravelly and stony, 4th rate.
Undergrowth, creosote.
Grazing, poor.
-
- From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., an iron post, 2 ins. diam., set, mkd., and witnessed as described in the official record of the resurvey of T. 22 S., R. 63 E.
- N. 4° 30' W., bet. secs. 34 and 35.
- Over rolling mountainous land, through scattered undergrowth; descend 20 ft. over short SW. slope.
- 2.70 Descend 250 ft. over broken NW. slope.
- 17.60 Service road to telephone line, bears NE. and SW.
- 20.52 Cable telephone line, bears N. 54° 51' E. and S. 54° 51' W.
- 22.00 Intersect line 1-4, Hydro No. 10 lode, Survey No. 4743, N. 41° 30' E. 4.52 chs. dist. from cor. No. 1
- 36.20 Wash, drains NE.
- 40.63 Proportionate point.
- Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
- ¼

S 34 | S 35

1943
- raise a mound
- of stone, 2 ft. base, 1½ ft. high, W. of cor.
- 43.30 Intersect line 2-1, Survey No. 4743, Hydro No. 8 lode, S. 46° 10' W. 4.03 chs. from cor. No. 2, identical with cor. No. 1 of Hydro No. 7 lode.
- 44.50 Wash, drains N. 10° W.
- 54.00 Enter stock pile, bears N. 20° W. and SE.; thence along W. end of same.