

546

Dependent Resurvey of the Subdivision of T. 21 S., R. 63 E.

Chains

79.33

Intersect the Fifth Standard Parallel South, on the S. bdy. of sec. 33, T. 20 S., R. 63 E., West 16.96 chs. (record dist.) from the stan. cor. of secs. 33 and 34, an iron post, 2 ins. diam., set, mkd., and witnessed as described in the official record.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 3, and 4, with brass cap mkd.

T 20 S R 63 E	
S 33	

S 4	S 3
T 21 S	R 63 E
C	C
1943	

raise a mound
of stone, 3 ft. base, 2 ft. high, S. of cor.

Land, rough and mountainous.
Soil, rocky, 4th rate.
Undergrowth, creosote.
Grazing, poor.

From the cor. of secs. 32 and 33 on the S. bdy. of the Tp., an iron post, 2 ins. diam., set, mkd., and witnessed as described in the official record of the resurvey of T. 22 S., R. 63 E.

N. 3° 02' W., bet. secs. 32 and 33.

Over nearly level flood plain, with a gradual N. to NW. drainage, through scattered undergrowth.

25.30

Graded and gravelled road, bears N. 84° 15' E. and S. 84° 15' W.

41.19

Proportionate point.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

	$\frac{1}{4}$	
S 32		S 33

1943		

raise a mound
of stone, 3 ft. base, 2 ft. high, W. of cor.

55.90

Dim road, bears N. 22° 30' W. and S. 22° 30' E.

82.37

Proportionate point, on NE. edge of flood plain, drains northwesterly.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 28, 29, 32, and 33, with brass cap mkd.

T 21 S R 63 E	
S 29	S 28

S 32	S 33
1943	

raise a mound
of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, nearly level with gradual N. to NW. slope and drainage.
Soil, gravelly, 3d rate.