

Dependent Resurvey of the Subdivision of T. 21 S., R. 63 E.

Chains	
49.20	Wash, drains N. 80° E.
72.00	Ascend 50 ft. over SE. slope.
77.40	Low ridge, bears NE., 1.00 ch. dist. to end, and SW., 7.00 chs. to end.
79.75	Intersect the Fifth Standard Parallel South, on the S. bdy. of sec. 32, T. 20 S., R. 63 E., West 17.20 chs. (record dist.) from the stan. cor. of secs. 32 and 33, an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.
	At point of intersection
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 4 and 5, with brass cap mkd.
	<div><div>T 20 S R 63 E</div><div>S 32</div><div>T 21 S R 63 E</div><div>S 5 S 4</div><div>C C</div><div>1943</div></div>
	raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.
	Land; mountainous and rolling. Soil, gravelly and rocky, 4th rate. Undergrowth, creosote. Grazing, poor.
	From the cor. of secs. 31 and 32, on the S. bdy. of the Tp., an iron post, 2 ins. diam., set, mkd., and witnessed, as described in the official record of the resurvey of T. 22 S., R. 63 E.
	N. 3° 05' W., bet. secs. 31 and 32.
	Over nearly level land, through scattered undergrowth; descend gradually over N. slope.
18.00	Graded road, bears N. 85° E. and S. 85° W.
39.86	The original ¼ sec. cor., mkd. by an old embedded mound of stone.
	At cor. point, in center of mound,
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	<div><div>1</div><div>¼</div><div>S 31 S 32</div><div>1943</div></div>
	raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	Thence
	N. 0° 53' W., beginning new measurement.
13.05	Service road along power line, bears N. 51° W. and S. 51° E.
13.70	Electric power line, bears same as road.