

4

Retracement of the Sixth Standard Parallel North, along a Portion of  
the South Boundary of T. 31 N., R. 24 E.

Chains

Along the Line Originally Surveyed by  
Hatch, Skinner, and Preble, Deputy Surveyors, in 1874.

Beginning at the SE. cor. of T. 31 N., R. 24 E., which is monumented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record.

West, on the S. bdy. of sec. 36, along the Sixth Standard Parallel North.

Over rolling bench land, through shadscale and sage undergrowth.

12.32

Fall 18 lks. S. of the original closing cor. of Ts. 30 N., Rs. 24 and 25 E., which is monumented with a lava stone, 10x8x6 ins., lying loose in a small mound of stone, mkd. with 6 notches on S., W., and E. edges.

I rehabilitate the corner by resetting the old corner stone in earth and stone mound.

Continue line and measurement.

17.35

Dry wash, 8 lks. wide, 1 ft. deep, drains N. 70° E.

40.00

Point for the standard  $\frac{1}{4}$  sec. cor. of sec. 36, at record distance; there is no remaining evidence of the original corner.

60.00

Low flat ridge, bears N. 80° E. and S. 80° W.

80.00

Point for the standard cor. of secs. 35 and 36, at record distance; there is no remaining evidence of the original corner.

Land, rolling.

Soil, sandy clay loam.

No timber; undergrowth, shadscale and sagebrush.

West, on the S. bdy. of sec. 35, along the Sixth Standard Parallel North.

Over gently rolling land, through shadscale and low sagebrush undergrowth.

5.10

Unimproved road, bears NW. and SE.

12.00

Low flat ridge, bears N. 80° W. and S. 80° E.

13.54

Fall 1.19 lks. S. of the original closing cor. of secs. 1 and 2, T. 30 N., R. 24 E., which is monumented with a lava stone, 18x15x8 ins., set in mound of stone, mkd. with 5 grooves on W., 1 groove on E., and 6 grooves on S. face.

I rehabilitate the corner by setting it more firmly and enlarging the mound of stone.

16.40

Unimproved road, bears NE. and S. 65° W.

40.00

Point for the standard  $\frac{1}{4}$  sec. cor. of sec. 35, at record distance; there is no remaining evidence of the original corner.

Asc. gradual, rolling E. slope.

65.00

Low flat spur, slopes S.; desc. over gradual SW. slope.