

E. BDY. T. 32 N., R. 24 E.

Chains

North, along the E. bdy. of sec. 12.

Ascend 25 ft. along W. side of side valley.

20.00 N. rim of side valley, bears NE. and SW.

31.00 S. rim of wash valley, bears NE. and SW.; descend 30 ft.

38.00 Dry run, 6 lks. wide, course NE.

40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 12, only.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

$$\begin{array}{r|l} \frac{1}{4} S 12 & \\ \hline & 1948 \end{array}$$

dig a circular trench, 6 ft. diam., and raise a mound of earth around post to top.

Ascend $3\frac{1}{4}$ ft. on S. slope.

42.60 Sandy ridge, N. edge of wash valley, bears N. 80° E. and S. 80° W.; descend 65 ft. on gentle NE. slope.

80.00 Point for the cor. of secs. 1 and 12 only.

Set an iron post 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{r|l} T32N & \\ S 1 & \\ \hline S 12 & \\ R24E & \end{array}$$

1948

dig a circular trench, 6 ft. diam., and raise a mound of earth around post to top.

Land, nearly level and slightly rolling, northerly drainage.
Soil, sandy clay loam, 2d rate.
Undergrowth, sagebrush and shadscale.
No timber.

North, along the E. bdy. of sec. 1.

Descend 20 ft. along gentle N. slope, thru undergrowth.

39.10 Clay bank, bears E. and W., faces S.

40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 1 only.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{r|l} \frac{1}{4} S 1 & \\ \hline & 1948 \end{array}$$

dig a circular trench, 6 ft. diam., and raise a mound of earth and stones around post to top.

Descend 20 ft. on gentle NE. slope.