

East Boundary of Ts. 31 and 32 N., R. 25 E.

Chains

For description and test of instruments, determination and verification of azimuth, and method of measurements refer to the field notes of the survey of the boundaries and subdivision of T. 33 N., R. 25 E., M.D.M., executed under this same assignment. The E. bdy. of Ts. 31 and 32 N., R. 25 E. was double chained and the mean of the measurements is given in the field notes.

EAST. BDY. OF T. 31 N., R. 25 E., M.D.M., NEVADA

Survey commenced at the standard cor. of T. 31 N., Rs. 25 and 26 E., an iron post, 3 ins. diam., set, mkd. and witnessed as described in the field notes of the independent resurvey of the Sixth Standard Parallel North, through R. 26 E.

North, bet. secs. 31 and 36.

Ascend 30 ft. over gentle S. slope, thru low undergrowth.

.90 Scraped road, bears N. 70° W. to Gerlach and S. 70° E.

16.10 Wash, 30 lks. wide, course SE.

37.00 Top of rise, bears SW. and NE.; descend 10 ft.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 36 and 31.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 36 \mid \text{S } 31 \\ 1948 \end{array}$$

dig a circular trench, 6 ft. diam., and raise a mound of earth around post to top.

Descend 15 ft. to

48.10 Wash, 20 lks. wide, course SW.; ascend 25 ft.

59.00 Low rise, bears NE. and SW.; descend 10 ft. to

63.00 Wash, 15 lks. wide, course SW.; continue along W. slope.

80.00 Point for the cor. of secs. 25, 30, 31 and 36.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T31N} \\ \text{R25E R26E} \\ \text{S } 25 \mid \text{S } 30 \\ \text{S } 36 \mid \text{S } 31 \\ 1948 \end{array}$$

dig a circular trench, 6 ft. diam., and raise a mound of earth around post to top.

Land, gently rolling, drains SW.
Soil, sandy clay loam, 2d rate.
Undergrowth, sagebrush and shadscale.
No timber.