

Dependent resurvey of a portion of the subdivision of T. 42 N., R. 25 E.

Chains

$$\frac{1}{4} \text{ S3 } \left| \right.$$

1946

22.50 Road, bears S. 80° E. and N. 80° W.

24.10 Wash, course S. 80° E.; asc. 140 ft. over S. slope.

41.74 The original $\frac{1}{4}$ sec. cor., a granite stone, 6x14x18 ins., loosely set in a mound of stone, and mkd. $\frac{1}{4}$ on W. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, with the original mkd. stone deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 2, with brass cap mkd.
$$\left| \frac{1}{4} \text{ S2 } \right.$$

1946

N. 0° 27' E., along the W. bdy. of sec. 2.

Asc. 110 ft. over S. slope changing to SE. slope.

17.00 Desc. 30 ft. over NW. slope.

20.64 Point 80.00 chs. in latitude from the cor. of secs. 3 and 10.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for cor. of lots 1 and 8, sec. 3, with brass cap mkd.

$$\text{S3 } \frac{1}{8} \left| \right.$$

1946

raise a

mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Desc. 130 ft. over NW. slope.

33.00 Ravine, course NE. along E. slope.

39.32 The cor. of secs. 2 and 3, on the S. bdy. of sec. 34, T. 43 N., R. 25 E., an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

Land, rolling mountainous and mountainous.

Soil, gravelly and rocky; 3rd rate.

Timber, none.

Undergrowth, sagebrush.

Grazing, none.

Completion of the Subdivision of T. 42 N., R. 25 E., M. D. M.

Beginning at the cor. of secs. 33 and 34, on the S. bdy. of the township.

North, on sectional guide meridian, bet. secs. 33 and 34.

Asc. 90 ft. over S. to SW. slope.

3.00 Along W. slope.

13.00 Desc. 80 ft. over steep NW. slope.