

Chains

Dependent Resurvey of the North Boundary of T.17N.,R.20E.

Reestablishment of the Survey Executed by
James S. Lawson, Deputy Surveyor in 1862.

The cor. of Tps. 17 and 18 N., Rs. 19 and 20 E., is mkd. by an iron post, 3 ins. diam., firmly set, with brass cap marked and witnessed as described in the 1943 resurvey record.

S. 88° 57' E., bet. secs. 6 and 31.

Over mountainous land through sagebrush and scattering juniper timber.

Ascend 20 ft. over gradual W. slope.

3.20 Spur, slopes N.; descend 340 ft. over NE. slope.

24.60 Ravine, 50 lks. wide, course NE.; ascend 140 ft. over NW. slope to $\frac{1}{4}$ sec. cor.

27.90 Old mining road, bears NE. and S. 20° W.

37.91 The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, marked by the original monument, a trap rock, 7x6x18 ins., firmly set, marked $\frac{1}{4}$ on N. face.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{S } 31 \\ \hline \frac{1}{4} \\ \text{S } 6 \\ 1947 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Bury the old corner stone alongside the iron post.

From this corner, Cor. No. 1, Lot No. 37, Orizaba lode, not patented, an old wood post, 4 x 4 x 30 ins. long, set in a mound of stone, mkd. No. 1 bears S. 5° 09' E., 26.38 chs. dist.

From the same corner, Cor. No. 1, Lot No. 38, Galena Hill lode, (patented) an old wood post, 6 x 8 x 30 ins. above ground, mkd. and witnessed as described in the official record, bears S. 22° 30' E., 15.23 chs. dist.

N. 89° 51' E., beginning new measurement.

Ascend 140 ft. over NW. slope.

6.30 Spur, slopes N.; descend 30 ft. along N. slope.

14.40 Ridge divide, bears NE. and SW.; descend 250 ft. over E. slope.

21.80 Ravine, course NE.; ascend 20 ft.

25.90 Ravine, course N.; ascend 270 ft. over NW. slope.