

Dependent Resurvey, T. 17 N., R. 20 E.

Chains	
6.10	Foot of mountain, bears NE. and S.70°W.; leave rolling land in Pleasant Valley; ascend 220 ft. over SE. slope.
20.60	Top of ascent at S. edge of bench, bears NE. and SW.; ascend 100 ft. across bench.
35.00	Foot of steep mountain, bears NE. and W.; ascend abruptly 130 ft. over SE. slope.
39.905	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, at proportionate distance. There is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ \\ S\ 6\ \ S\ 5 \\ \\ 1947 \end{array}$ Raise a mound of stone, 3 ft. base, 2 ft. high, <u>east</u> of corner. Ascend 460 ft. over steep SE. slope.
67.90	Ridge divide, bears NE. and SW.; descend 120 ft. over NW. slope.
78.86	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp. Land, rolling on the south 6 chs.; remainder mountainous. Soil, rocky and gravelly, 4th rate. Timber, none; undergrowth, sagebrush.
Retracement of Mineral Survey No. 4291 Bargo Lode, surveyed by William A. Simkins, U.S. Mineral Surveyor in 1916. Beginning at cor. No. 1 of the Bargo lode, from which the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., bears S. 20° 31' E., 11.89 chs. dist. N. 46° W., along line 1-2.	
9.595	Cor. No. 2. N. 40° 42' E., along line 2-3.
22.29	Cor. No. 3. S. 49° 27' E., along line 3-4.
9.00	Cor. No. 4. S. 39° 16' W., along line 4-1.
22.87	Cor. No. 1, the place of beginning.

GENERAL DESCRIPTION

Township 17 North, Range 20 East, of the Mount Diablo