Resurvey of the West Bdy. of T. 21 S., R. 54 E.

Chains	This cor. is situated on the W. edge of the road.
	Land, level. Soil, clay. Timber, mesquite. Undergrowth, shadscale.
	N. 3° 05' W., along the W. bdy. of sec. 6.
	Through low shadscale along W. edge of N. and S. road.
3.60	Road bears NW. and S.
4.20	Waste ditch, dry, 5 lks. wide, 12 ft. deep, course NW.
5.40	Old waste ditch, dry, with mesquite lined banks, NW. Continue over open flat.
12.00	Shallow drain, course W.
25.20	Dirt road, fair condition, bears N. 80° W.
38.61	Point for the ½ sec. cor. of sec. 1 only, 40 chs. in latitude from the cor. of secs. 1 and 12.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	4 S 1
t ·	1948
	from which
	Drilled well, 10 inch steel casing, 242 ft. to water, bears S. 81° 45' W., 3.22 chs. dist.
	Bury a stone, 4x6x7 ins. mkd. X alongside iron post and raise small flat mound of stone around post.
39.21	Point for the \$\frac{1}{4}\$ sec. cor. of secs. 1 and 6, at proportionate dist. No evidence remains of the original mound and pits. A mesquite post 2 ins. diam., 4 ft. long, mkd. \$\frac{1}{4}\$, lying loose; bears E. \$\frac{1}{4}\$ lks. dist. This cor. is changed to a \$\frac{1}{4}\$ sec. cor. of sec. 6 only.
	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	. 1948
•	Bury a stone 4x5x6 ins., mkd. X and reset the orig. post alongside the iron post.
39.65	Waste ditch, 5 lks. wide, water 1 ft. deep, course W.
65.80	Wash, 10 lks. wide, course SW.
78.79	The original closing cor. of Ts. 21 S., Rs. 53-54 E., monumented with a brass tablet seated in the top of a concrete post 13 ins. diam., 8 ins. above ground, with a squared mesquite post illegibly scribed, 3 ins. diam., 16 ins. above ground; and a juniper post 8 ins. diam., 4 ft. above ground set alongside: This cor. was remonumented in 1926 by the GLO in cooperation with the