

T. 21 S., R. 53 E.

Chains

North, bet. secs. 1 and 2, on sectional guide meridian.

Over level land thru scattered mesquite.

9.70 Desert road, bears N. 70° E. and S. 70° W.

37.90 Waste ditch, 8 lks. wide, water 1 ft. deep, course S. 76° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \hline \text{S2} \quad | \quad \text{S1} \\ \hline 1948 \end{array}$$

dig a circular trench and raise mound of earth around post.

80.54 Intersect the 5th Standard Parallel South.

Point for the closing cor. of secs. 1 and 2.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T20S} \quad \text{R53E} \\ \hline \text{S36} \\ \hline \text{S2} \quad | \quad \text{S1} \\ \hline \text{T21S} \quad \text{R53E} \\ \hline \text{CC} \\ 1948 \end{array}$$

dig pits, 18x18x12 ins., E., W., and S. of post, 3 ft. dist.

From the point of intersection, the standard cor. of secs. 35 and 36, T. 20 S., R. 53 E., bears N. 89° 50' W., 10.95 chs. dist.

Land, level.

Soil, clay, and silt.

Undergrowth, mesquite.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 1 is at 40.00 chs. from the NW. cor. of the sec. and on the Fifth Standard Parallel South.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \text{ S1} \\ \hline 1948 \end{array}$$

dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.

From this cor. the stan. $\frac{1}{4}$ sec. cor. of sec. 36, T. 20 S., R. 53 E., bears N. 89° 35' W., 10.73 chs. dist.

From the cor. of secs. 25, 26, 35 and 36.

West, on auxiliary base line, bet. secs. 26 and 35.