

T. 21 S., R. 53 E.

Chains

From the point of intersection, the stan. cor. of secs. 34 and 35, T. 20 S., R. 53 E., bears N. 89° 52' W., 11.83 chs. dist.

Land, level.
Soil, clay and silt.
Undergrowth, shadscale.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 2 is at midpoint and on the 5th Stan. Parallel South.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 2

1948

dig pits, 18x18x12 ins., E. and W. of iron post, 3 ft. dist.

From this cor. the stan. $\frac{1}{4}$ sec. cor. of sec. 35, T. 20 S., R. 53 E., bears N. 89° 52' W., 11.39 lks. dist.

From the cor. of secs. 22, 23, 26 and 27.

West, bet. secs. 22 and 27, on auxiliary base line.

Over gently rolling land, through scattered greasewood and shadscale.

3.10 Shallow drain, 15 lks. wide, course N. 20° W.

5.00 Low flat spur, slopes NW.

12.20 Desert road, bears N. 15° E., and S. 15° W.

18.50 Drain, course SW.

30.00 Drain, 5 lks. wide, course SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S 22

$\frac{1}{4}$ S 27

1948

raise flat mound of stone and earth, 3 ft. in diam., around post.

41.50 Drain, 5 lks. wide, course S. 10° W.

55.00 Saddle, between two low hills, bears N. and S.

67.00 Wash, 10 lks. wide, course S. 20° W.; asc. 60 ft. over E. slope.

77.50 Top of low long hill, near S. end, bears N. 60° W.; desc. 15 ft. over SW. slope.