

DEPENDENT RESURVEY OF A PORTION OF THE S. BDY., T. 12 N., R. 36 E. 3

CHAINS	
81.16	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.</p> <div>T12N R36E S 31   S 32 S 6   S 5 T11N 1962</div> <p>Land, level. Soil, sand. Timber, none; undergrowth, creosote brush.</p> <hr/> <p>S. 89° 33' W., bet. secs. 6 and 31.</p> <p>Over low sand dunes.</p> <p>5.00 Leave sand dunes, over level desert land.</p> <p>16.80 Wash, 15 lks. wide, 3 ft. deep, drains SW.</p> <p>40.58 Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.</p> <div>T12N R36E ¼ S 31 S 6 T11N 1962</div> <p>80.34 The cor. of Tps. 11 and 12 N., Rs. 35 and 36 E., monumented with a wooden stake, 14x1x1 ins.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.</p> <div>T12N R35E R36E S 36   S 31 S 1   S 6 T11N 1962</div> <p>Bury the original corner stake alongside the iron post.</p> <p>Raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.</p> <p>Land, level. Soil, sand. Timber, none; undergrowth, creosote brush.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE E. BDY., T. 12 N., R. 36 E.</p> <hr/> <p>Reestablishment of the survey executed by T. K. Stewart and S. M. Morrison, Deputy Surveyors, in 1883.</p>