

DEPENDENT RESURVEY OF A PORTION OF THE E. BDY., T. 12 N., R. 36 E.

CHAINS

Asc. 320 ft. over SW. slope.

82.20

Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top of cap, with brass cap mkd.

T12N
R36E R37E
S 1 | S 6
S 12 | S 7
1962

Land, mountainous.

Soil, clay and exposed granite.

Timber, none; undergrowth, creosote brush and cacti.

N. $0^{\circ} 20'$ E., bet. secs. 1 and 6.

Over mountainous land; asc. 50 ft. over S. slope.

3.20

Ridge, bears E. and W.; desc. 720 ft. over steep N. slope.

27.00

Base of desc.; bears E. and W.; desc. gradual N. slope.

41.10

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T12N
R36E R37E
 $\frac{1}{4}$
S 1 | S 6
1962

54.40

Trail road, bears E. and W.

82.20

The cor. of Tps. 12 and 13 N., Rs. 36 and 37 E., monumented with basalt stone, 20x14x12 ins., plainly mkd. and firmly set.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground and in a collar of stone with brass cap mkd.

T13 N
R36E R37E
S 36 | S 31
S 1 | S 6
T12N
1962

Bury the original corner stone alongside the iron post.

Land, mountainous and rolling.

Soil, clay, sandy loam, and exposed granite.

Timber, none; undergrowth, creosote brush, cacti, and thistle.