

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 36 E.

Reestablishment of the Survey Executed by T.K. Stewart
and G. W. Conkling, Jr., Deputy Surveyors, in 1883.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy.
of the tp.

S. 89° 56' W., bet. secs. 24 and 25.

Over mountainous land; asc. 180 ft. over NE. slope.

21.40 Spur, slopes NE.; desc. 130 ft. over NW. slope.

40.18 Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in
the ground to bedrock and in a mound of stone, 4 ft. base
to top of cap, with brass cap mkd.

	T12N	R36E
	$\frac{1}{4}$	<u>S 24</u>
		S 25
		1962

Desc. 140 ft. over NW. slope.

53.00 Head of ravine, drains NW.; asc. 270 ft. over broken E.
slope.

75.30 Spur, slopes NW.; desc. 140 ft. over SW. slope.

80.36 The cor. of secs. 23, 24, 25 and 26, monumented with a
basalt stone, 12x10x6 ins., dimly mkd. and firmly set.

At the corner point.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in
the ground and in a mound of stone, 4 ft. base to top of
cap, with brass cap mkd.

	T12N	R36E
	<u>S 23</u>	<u>S 24</u>
	S 26	S 25
		1962

Bury the original corner stone alongside the iron post.

Land, mountainous.

Soil, clay loam.

Timber, none; undergrowth, creosote brush and cacti.

N. 0° 04' E., bet. secs. 23 and 24.

Over mountainous land; asc. 100 ft. over SW. slope.

4.80 Spur, slopes NW; desc. 630 ft. over broken NE. slope.

30.90 Trail road, bears NW. and SE.

32.10 Wash, 20 lks. wide, 4 ft. deep, drains NW.; asc. 80 ft.
over S. slope.