

## DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES

3

CHAINS

Dependent Resurvey of a portion of the Subdivisional Lines  
Of T. 12 N., R. 37 E.

Re-establishment of the survey executed by Stewart  
and Morrison, Deputy Surveyors, in 1881.

From the cor. of secs. 20, 21, 28 and 29, monumented with  
a granite of stone, 10x6x4 ins., plainly mkd. and firmly  
set.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in  
the ground and in a mound of stone, 4 ft. base to top of  
cap, with brass cap mkd.

T12N	R37E
S 20	S 21
S 29	S 28
1962	

Bury the original corner stone alongside the iron post.

N. 0° 16' W., bet. secs. 20 and 21.

Over mountainous land; desc. 670 ft. over N. slope.

32.80 Base of mountain, bears NE. and SW. over rolling land;  
desc. gradual N. slope.

39.19 Point selected for the witness ¼ sec. cor. of secs. 20  
and 21.

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in  
the ground and in a mound of stone, 4 ft. base to top of  
cap, with brass cap mkd.

T12N	R37E
¼	
W	C
S 20	S 21
1962	

40.19 Point for the ¼ sec. cor. of secs. 20 and 21, at propor-  
tionate distance, falls on S. slope of a mine dump where  
the cor. cannot be perpetuated.

Over mining area.

52.00 Leave mine dumps.

80.38 The cor. of secs. 16, 17, 20 and 21, monumented with a  
limestone, 12x10x8 ins., plainly mkd. and firmly set.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in  
the ground and in a collar of stone, with brass cap mkd.

T12N	R37E
S 17	S 16
S 20	S 21
1962	

Bury the original corner stone alongside the iron post.  
Land, mountainous S. ½ mile, rolling N. ½ mile.  
Soil, sandy loam, gravel.