

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R39E  
SC  
¼ S 33  
1962

Bury the original wood post alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N. 89° 55' W., beginning new measurement.

Over gently rolling reseeded land.

40.52

The standard cor. of secs. 32 and 33, monumented with a stone, 18x12x2 ins., plainly mkd. SC on the N. face, 4 notches on the E. face and 2 notches on the W. face and firmly set in a mound of stone.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R39E  
SC  
S 32 | S 33  
1962

Bury the original corner stone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.

Land, gently rolling.

Soil, sandy clay.

Undergrowth, crested wheat grass.

Dependent Resurvey of a portion of the East boundary, T. 41 N., R. 39 E., Mount Diablo Meridian, Nevada.

Re-establishment of the survey executed by William Epler, Deputy Surveyor, in 1867.

The cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., determined by a small steel rod in the center of gravel road, bearing E. and W. and in line with property fence to the S.

At the corner point

Set a copperweld, 24 ins. long, ½ ins. diam., 14 ins. underground, with a brass cap mkd.

T41N  
R39E R40E  
S 24 | S 19  
S 25 | S 30  
1962

from which: