

CHAINS

Dependent Resurvey of a portion of the E. Bdy. of T. 42 N., R. 39 E., Mount Diablo Meridian, Nevada.

Re-establishment of the survey executed by William Epler, Deputy Surveyor, in 1867.

Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T42N	
R39E	R40E
S 1	S 6
S 12	S 7
1962	

from which

Corner of fence, bearing N. and S., bears E. 28 lks. dist.

Raise a mound of stone, 3 ft. base, 2 ft. high, 1W of cor.

From this cor., the cor. of secs. 7, 12, 13 and 18, monumented with an unmarked granite stone, 6x8x36 ins., firmly set, bears S. $0^{\circ} 06' E.$, 80.22 chs. dist. This position has long been recognized as the cor. by adjacent landowners.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T42N	
R39E	R40E
S 12	S 7
S 13	S 18
1962	

from which

Corner of fences, bearing N. and E., bears N. $34^{\circ} E.$, 24 lks. dist.

Corner of fences, bearing S. and W., bears S. $50^{\circ} 54' W.$, 41 lks. dist.

Bury the original cornerstone alongside the iron post.

N. $0^{\circ} 06' W.$, bet. secs. 1 and 6.

Over gently rolling land, through medium undergrowth, along wash and W. side of fence.

40.11 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, as determined by the corner of fences bearing N., W., and E.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.