

CHAINS

Corner is located on a fence, 4-strand barbwire, bears N. and S.

Land, gently rolling.
Soil, sandy clay and rocky.
Undergrowth, picklebrush.

Dependent Resurvey of a portion of the Subdivisional Lines of T. 43 N., R. 39 E., Mount Diablo Meridian, Nev.

Reestablishment of the surveys executed by O. A. Palmer, Deputy Surveyor, in 1868, and Fisher and Morrison, Deputy Surveyors, in 1882.

From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 42 N., R. 39 E.

N. 0° 36' W., bet. secs. 35 and 36.

Over gently rolling land, through medium undergrowth.

- 4.00 Wash, 10 lks. wide, 2 ft. deep, drains S. 20° W.
- 18.50 Trail road, bears N. 20° E. and S. 5° W.
- 21.30 Wash, 20 lks. wide, 1 ft. deep, drains SW.
- 26.20 Mullinix Creek, 50 lks. wide, 2 ft. deep, drains S. 20° E.
- 40.31 Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T43N R39E
S 35 | S 36
1962

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

- 53.30 Coleman Creek, 50 lks. wide, 2 ft. deep, drains S. 5° E.

- 80.62 The cor. of secs. 25, 26, 35 and 36, monumented with a sandstone, 12 x 10 x 6 ins., firmly set, and plainly mkd. with 1 notch on the E. face and 1 notch on the S. face.

At the corner point,

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a large collar of stone, with brass cap mkd.

T43N R39E
S 26 | S 25
S 35 | S 36
1962

Bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.