

DEPENDENT RESURVEY, N. BDY., T. 44 N., R. 41 E.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to cap, with brass cap mkd.

T45N	R41E
S 33	S 34
S 4	S 3
T44N	
1963	

raise a mound of stone, 3½ ft. base, 3 ft. high, W. of cor.

Land, rolling.
Soil, sandy loam and rocky.
Undergrowth, sagebrush and shadscale.

N. 88° 07' W., bet. secs. 4 and 33.

Over rolling land, through medium undergrowth; desc. 30 ft. over NW. slope.

- 4.20 Ravine, drains N. 20° E.; asc. 60 ft. over SE. slope.
16.30 Spur, bears N. 30° E.; desc. 50 ft. over NW. slope.
40.85 Wash, 10 lks. wide, 2 ft. deep, drains NE.
40.95 Point for the ¼ sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T45N	R41E
¼ S 33	
S 4	
T44N	
1963	

raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.

Asc. 80 ft. over general E. slope.

- 72.50 Trail road, bears S. and N. 30° W.
81.89 Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 5 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T45N	R41E
S 32	S 33
S 5	S 4
T44N	
1963	

from which

Point for the cor. of Tps. 44 and 45 N., Rs. 40 and 41 E., at proportionate distance; there is no