

DEPENDENT RESURVEY, S. BDY., T. 44 N., R. 41 E.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T44N R41E  
 $\frac{1}{4}$   $\frac{S \ 32}{S \ 5}$   
 T43N  
 1963

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Continue over rolling land.

59.79 Point for the W. 1/16 sec. cor. of secs. 5 and 32, at midpoint.

Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

T44N R41E  
 W 1/16  $\frac{S \ 32}{S \ 5}$   
 T43N  
 1963

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

70.20 Rim of Martin Creek, bears SE. and NW.; desc. 220 ft. over steep SW. slope.

76.50 Martin Creek, 50 lks. wide, course SE.; asc. 90 ft. over steep NE. slope.

79.02 Point selected for the witness cor. of secs. 5, 6, 31 and 32.

Set an iron post, 28 ins. long, 2½ ins. diam., 2 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T44N R41E  
 W  $\frac{S \ 31}{S \ 6}$  |  $\frac{S \ 32}{S \ 5}$   
 C  
 T43N  
 1963

79.72 Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; falls on steep slope where corner cannot be perpetuated; there is no remaining evidence of the original corner.

Land, low mountainous.  
 Soil, sandy loam and rocky.  
 Undergrowth, sagebrush.

S. 89° 56' W., bet. secs. 6 and 31.

Over low mountainous land, through medium undergrowth; asc. 360 ft. over NE. slope.

11.60 Rocky spur, projects SE.; desc. 130 ft. over W. slope.

19.93 Point for the E. 1/16 sec. cor. of secs. 6 and 31, at midpoint.