

NINTH STANDARD PARALLEL NORTH, R. 41 E.

CHAINS

Retracement and Partial Dependent Resurvey of the Ninth Standard Parallel North, through R. 41 E., MDM, Nevada.

Re-establishment of the Survey executed by
W. D. Minckler, Deputy Surveyor, in 1882

Beginning at the standard corner of T. 46 N., Rs. 41 and 42 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 45 N., R. 42 E.

West, along the S. bdy. of sec. 36.

Over mountainous land, through medium undergrowth; asc. 180 ft. over E. slope.

6.19 The closing cor. of T. 45 N., Rs. 41 and 42 E., hereinafter described.

Asc. 70 ft. over E. slope.

9.90 Spur, bears S. 20° W.; desc. 380 ft. over SW. slope.

23.95 Seep spring, on line, in wash, drains S.; asc. 100 ft. over SE. slope.

34.40 Rocky spur, bears S. 20° W.; desc. 80 ft. over SW. slope.

39.00 Base of descent, bears S.

39.73 The standard ¼ sec. cor. of sec. 36, monumented with a stone, 20x14x8 ins., firmly set in a mound of stone and plainly mkd. ¼ on the N. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.

SC
T46N R41E
¼ S 36

1962

bury the original cornerstone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.

S. 89° 55' W., beginning new measurement.

Asc. 40 ft. over SE. slope.

5.50 Spur, bears S. 20° W.; desc. 170 ft. over SW. slope.

5.95 The witness ¼ sec. cor. of sec. 1, only, hereinafter described.

6.45 True point for the ¼ sec. cor. of sec. 1, T. 45 N., R. 41 E., hereinafter described.

13.30 Ravine, drains S. 20° E.; asc. 70 ft. over SE. slope.