

NINTH STANDARD PARALLEL NORTH, R. 40 EAST

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T46N R40E
S 36
 S 1 | S 6
 T45N
 R40E R41E
 CC
 1963

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the cor. of Tps. 44 and 45 N., Rs. 40 and 41 E., an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 44 N., R. 41 E., bears S. $0^{\circ} 18' E.$, 482.97 chs. dist.

4.00 Wash, 10 lks. wide, 1 ft. deep, drains S.; continue over rolling land, draining SE.

26.30 Ravine, drains S. $60^{\circ} E.$

40.44 The standard $\frac{1}{4}$ sec. cor. of sec. 36, monumented with a basalt stone, 14x12x10 ins., firmly set in a mound of stone and plainly mkd. $\frac{1}{4}$ on the N. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

SC
 T46N R40E
 $\frac{1}{4}$ S 36

1963

bury the original cornerstone alongside the iron post.

Land, rolling.

Soil, sandy, clay and rocky.

Undergrowth, sagebrush and shadscale.

Dependent Resurvey of the E. Bdy. of T. 45 N., R. 41 E.
 Mount Diablo Meridian, Nevada

Re-establishment of the survey executed by Smyles
 and Fitzpatrick, Deputy Surveyors, in 1883

Beginning at the cor. of Tps. 44 and 45 N., Rs. 41 and 42 E. an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 44 N., R. 42 E.

N. $0^{\circ} 13' W.$, bet. secs. 31 and 36.

Over rolling land, draining E., through medium undergrowth.

Desc. 40 ft. over N. slope.