

DEPENDENT RESURVEY, E. BDY., T. 44 N., R. 42 E

CHAINS	
	<p>Land, gently rolling. Soil, sandy loam and rocky. Undergrowth, sagebrush and budsage.</p>
	<p>N. 0° 15' W., bet. secs. 7 and 12.</p> <p>Over gently rolling land, through medium undergrowth.</p>
7.70	<p>Nevada Northern Gas Co., pipeline, bears N. 55° 45' E. and S. 55° 45' W.</p>
40.15	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with a basalt stone, 12x8x4 ins., firmly set and dimly mkd. 1/4 on the W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T44N R42E R43E S 12 S 7 1963</p> </div> <p>reset the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<p style="text-align: center;">—————</p> <p>NORTH, beginning new measurement.</p> <p>Over gently rolling land.</p>
39.99	<p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T44N R42E R43E S 1 S 6 S 12 S 7 1963</p> </div> <p>raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p> <p>Land, gently rolling. Soil, sandy loam. Undergrowth, sagebrush.</p>
	<p>NORTH, bet. secs. 1 and 6.</p> <p>Over gently rolling land.</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground with brass cap mkd.</p>