

DEPENDENT RESURVEY, S. BDY. T. 44 N., R. 42 E.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.

T44N R42E
 $\frac{S \ 31}{S \ 6} \mid \frac{S \ 32}{S \ 5}$
 T43N
 1962

raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Land, rolling.
 Soil, sandy, clay and rocky.
 Undergrowth, sagebrush.

N. 89° 41' W., bet. secs. 6 and 31.

Over rolling land, through medium undergrowth.

- 9.00 Wash, 10 lks. wide, 1 ft. deep, drains SE.
- 10.70 Graded road, bears SE. and NW.
- 23.10 Same road, bears N. 25° E. and S. 70° W.; wash, 10 lks. wide, 1 ft. deep, drains S. 10° W.
- 27.30 Graded road, bears N. 20° E. and S. 20° W.
- 40.31 Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. daim., 24 ins. in the ground, with brass cap mkd.

T44N R42E
 $\frac{1}{4} \frac{S \ 31}{S \ 6}$
 T43N
 1962

raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.

Continue over rolling land.

- 70.90 Wash, 10 lks. wide, 2 ft. deep, drains SE.
- 79.44 The cor. of Tps. 43 and 44 N., Rs. 41 and 42 E., monumented with a stone, 14x10x6 ins., firmly set in a mound of stone and plainly mkd. 6 notches on the E. and W. faces.

At the corner point

Set an iron post, 28 ins. long, 2½ ins.diam., 24 ins. in the ground, with brass cap mkd.

T44N
 R41E R42E
 $\frac{S \ 36}{S \ 1} \mid \frac{S \ 31}{S \ 6}$
 T43N
 1962