

DEPENDENT RESURVEY OF THE NINTH STANDARD PARALLEL
NORTH, NORTH BOUNDARY T. 45 N., R. 42 E.

CHAINS

Dependent Resurvey of the Ninth Standard Parallel
North, through R. 42 E., Mount Diablo Meridian,
Nevada.

Re-establishment of the survey executed by Smyles
and Fitzpatrick, Deputy Surveyors, in 1883.

The standard corner of T. 46 N., Rs. 42 and 43 E., monu-
mented with the original basalt stone, 8x8x6 ins., plainly
mkd. with 6 notches on the E. and W. faces, with mound
of stone to N. This is the standard township corner
although the field notes describe a wooden post.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in
the ground, with brass cap mkd.

SC
T46N
R42E R43E
<u>S 36 S 31</u>
1962

bury the original cornerstone alongside the iron post
and raise a mound of stone, 4 ft. base, 3 ft. high, N.
of cor.

S. 89° 59' W., along the S. bdy. of sec. 36.

Over gently rolling land, through medium undergrowth.

20.15 The closing corner of T. 45 N., Rs. 42 and 43 E., here-
inafter described.

40.71 The standard ¼ sec. cor. of sec. 36, monumented with the
remains of the original wooden post, set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in
the ground, with brass cap mkd.

SC
T46N R42E
<u>¼ S 36</u>
1962

reset the original wooden post, alongside the iron post
and raise a mound of stone, 3½ ft. base, 2 ft. high,
N. of cor.

N. 89° 55' W., beginning new measurement.

Over gently rolling land.

14.915 The N. ¼ sec. cor. of sec. 1, hereinafter described.

25.80 Trail road, bears NE. and SW.

27.50 Creek, 20 lks. wide, 1 ft. deep, course NE.

39.89 The standard cor. of secs. 35 and 36, monumented with a
wooden post, 2x4x30 ins. long, plainly scribed S 35 on
the W. face.