

DEPENDENT RESURVEY, T. 45 N., R. 42 E.

CHAINS		
	<p style="text-align: center;">T45N R42E S 1/16 S 5 S 4 1962</p>	
40.00	Ravine, drains E.	
40.36	<p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, monumented with a trapstone, 10x8x4 ins., firmly set in a mound of stone and plainly mkd. $\frac{1}{4}$ on the W. face. This is the $\frac{1}{4}$ sec. cor. although the field notes describe a post with a mound of earth.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T45N R42E S $\frac{1}{4}$ S 4 1962</p> <p>bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $9^{\circ} 21'$ W., beginning new measurement.</p> <p>Over rolling land.</p>	
17.50	Ravine, drains NE.	
30.00	Wash, 10 lks. wide, 1 ft. deep, drains NE.	
48.10	Wash, 20 lks. wide, 2 ft. deep, drains N. 70° E.	
54.08	<p>Intersect the Ninth Standard Parallel N.</p> <p>Point for the closing cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T46N R42E <u>S 32</u> S 5 S 4 CC T45N 1962</p> <p>raise a mound of stone, 3 ft. base, 3 ft. high, S. of cor.</p> <p>From this cor. the standard cor. of secs. 32 and 33, bears S. $89^{\circ} 39'$ E., 10.27 chs. dist.</p> <p>Land, rolling. Soil, sandy clay and rocky. Timber, none; undergrowth, sagebrush.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>The point for the N. $\frac{1}{4}$ sec. cor. of sec. 4 is on the Ninth Standard Parallel N. and at midpoint on the N. bdy. of sec. 4.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	