

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 39 N., R. 54 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} \text{T39N R54E} \\ \text{S } 31\frac{1}{4} \text{ S } 32 \\ \hline \text{S } 5 \\ \text{T38N} \end{array}$ <p>1963</p> <p>bury the original cornerstone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.</p> <hr/> <p>S. $89^{\circ} 46'$ W., along the S. bdy. of sec. 31.</p> <p>Over rolling land, through medium undergrowth; desc. gradually over a N. slope.</p> <p>7.00 Wash, 30 lks. wide, 3 ft. deep, drains NNE.</p> <p>7.26 The closing corner of secs. 5 and 6, T. 38 N., R. 54 E., monumented with a basalt stone, 16 x 8 x 8 ins., mkd. with 5 notches on the E. edge, 1 notch on the W. edge, CC on the S. face and firmly set in the ground, bears SOUTH .01 chs. dist.</p> <p>15.00 Wash, 30 lks. wide, 2 ft. deep, drains SE.; asc. 150 ft. over an E. slope.</p> <p>39.80 Spur, slopes S.; desc. 20 ft. over a W. slope.</p> <p>39.85 The $\frac{1}{4}$ sec. cor. of sec. 31, monumented with a basalt stone, 12 x 12 x 12 ins., mkd. $\frac{1}{4}$ on the N. face and firmly set in the ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> $\begin{array}{r} \text{T39N R54E} \\ \frac{1}{4} \text{ S } 31 \\ \hline \text{T38N} \end{array}$ <p>1963</p> <p>bury the original cornerstone and set a steel fence post, 6 ft. long, 16 ins. in the ground, alongside the iron post.</p> <hr/> <p>S $89^{\circ} 54'$ W., beginning new measurement</p> <p>Over rolling land, through medium undergrowth; desc. 20 ft. over a W., slope.</p>