

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 39 N., R. 54 E., MDM, NEVADA

CHAINS

39.96

The cor. of secs. 1, 6, 7 and 12, monumented with a basalt stone, 16 x 8 x 6 ins., mkd. with 5 grooves on the S. face and 1 groove on the N. face and firmly set in the ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T39N
R53E R54E
S 1 | S 6
S 12 | S 7

1963

bury the original cornerstone alongside the iron post.

This corner is located at the corner of fence, from which fences bear N. and W.

N. $0^{\circ} 04'$ E., bet. secs. 1 and 6.

Over mountainous land, through medium undergrowth; asc. 30 ft. over a SE. slope; along a fence.

11.20 Corner of fences, from which fences bear S. and E.; asc. 100 ft. over a SE. slope.

24.00 Spur, slopes ENE.; desc. 230 ft. over a N. slope.

31.70 Gance Creek, 15 lks. wide, 1 ft. deep, course E.; asc. 20 ft. over a S. slope.

34.60 Bladed road, bears E. and W.; asc. 70 ft. over a S. slope.

39.10 Graded road, bears E. and W.; asc. 20 ft. over a SW. slope.

40.07 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with a basalt stone, 18 x 10 x 4 ins., mkd. $\frac{1}{4}$ on the W. face and firmly set in the ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T39N
R53E R54E
 $\frac{1}{4}$
S 1 | S 6

1963