

DEPENDENT AND INDEPENDENT RESURVEY OF  
THE SUBDIVISIONAL LINES,  
T. 39 N., R. 54 E., MDM, NEVADA

CHAINS	
35.70	Fence, bears ENE. and WSW.; asc. 50 ft. over a S. slope.
65.33	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 35 and 36, determined at record distance in latitude from the cor. of secs. 13, 14, 23 and 24, and on line bet. the cor. of secs. 25, 26, 35 and 36; and the cor. of secs. 35 and 36 on the S. bdy. of the Tp.; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T39N R54E <math>\frac{1}{4}</math> S 35 S 36</p> <p style="text-align: center;">1968</p> <p>raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.</p>
86.10	Trail road, bears E. and W.; asc. 150 ft. over a S. slope.
100.00	Top of rock butte; desc. 130 ft. over a NE. slope.
105.37	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T39N R54E <u>S 26 S 25</u> S 35 S 36</p> <p style="text-align: center;">1968</p> <p>raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p>
22.60	<p>From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp., monumented with an iron post, <math>2\frac{1}{2}</math> ins. diam., firmly set and exposed 8 ins. above the ground, mkd. as described in the field notes of the dependent resurvey of T. 39 N., R. 55 E., executed under this same group.</p> <p>N. <math>75^{\circ} 42'</math> W., bet. secs. 25 and 36.</p> <p>Over rolling land, through medium undergrowth; asc. 60 ft. over a S. slope.</p> <p>Ridge, bears ENE. and SW.; desc. 90 ft. over a W. slope.</p>