

DEPENDENT AND INDEPENDENT RESURVEY OF
THE SUBDIVISIONAL LINES,
T. 39 N., R. 54 E., MDM, NEVADA

CHAINS	
44.00	Low ridge, bears E. and W.; desc. over a gentle N. slope.
80.16	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{T39N R54E} \\ \text{S 23 S 24} \\ \hline \text{S 26 S 25} \end{array}$
	1968
	raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.
	<hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 8 ins. above the ground, mkd. as described in the field notes of T. 39 N., R. 55 E., executed under this same group.</p>
	N. 77° 32' W., bet. secs. 24 and 25.
	Over rolling land, through medium undergrowth.
34.50	Trail road, bears ESE. and WNW.
34.70	Wash, 15 lks. wide, 2 ft. deep, drains ESE.
41.30	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{T39N R54E} \\ \text{S 24} \\ \frac{1}{4} \text{---} \\ \text{S 25} \end{array}$
	1968
	raise a mound of stone, 4 ft. base, 2 ft. high, N. of cor.
	From this corner, the N. end of an earth dam of a reservoir, bears S. 67° 50' E., 11.50 chs. dist.; reservoir extends 2 chs. WNW.
	Asc. 70 ft. over a gentle E. slope.
82.60	The cor. of secs. 23, 24, 25 and 26.