442

DEPENDENT AND INDEPENDENT RESURVEY OF
THE SUBDIVISIONAL LINES,
T. 39 N., R. 54 E., MDM, NEVADA

CHAINS	
	N. 1° 54' E., beginning new measurement.
	Over rolling land; through reseeded area.
8.20	Wash, 15 lks. wide, 2 ft. deep, drains E.
33.50	Wash, 15 lks. wide, 2 ft. deep, drains SE.
39.97	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T39N R54E S 11 | S 12 S 14 | S 13
	1968
	raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above the ground, mkd. as described in the field notes of the dependent resurvey of T. 39 N., R. 55 E., executed under this same group.
	N. 82° 59' W., bet secs. 12 and 13.
	Over rolling land, through reseeded area.
9.50	Wash, 15 lks. wide, 2 ft. deep, drains ENE.
17.00	Trail road, bears N. and S.
40.15	Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T39N R54E ¼ S 12 S 13
	1968
	raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.
	From this corner, the N. end of an earth dam of a reservoir, bears S. 79° 20' E., 21.80 chs. dist.; reservoir extends 2 chs. W.
80.30	The cor. of secs. 11, 12, 13 and 14.

U.S. Government Printing Office-1978-778-206/433