

SURVEY OF TRACT NO. 37,
T. 39 N., R. 54 E., MDM, NEVADA

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T39N R54E
S 5
AP 1 | AP 2
TR 38 | TR 37

1978

S. $0^{\circ} 18'$ E., along line 2-3, Tract No. 37 and line 1-4, Tract No. 38.

- 1.00 Gravel road, bears E. and WSW.
- 6.00 Fence, bears E. and W.
- 14.00 Gance Creek, 15 lks. wide, 2 ft. deep, course E.
- 19.92 Point for Angle Point No. 3, Tract No. 37, identical with Angle Point No. 4, Tract No. 38, Angle Point No. 2, Tract No. 39 and the C-W $1/16$ sec. cor. of sec. 5, as surveyed by U. S. Deputy Surveyor, H. B. Maxson.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T39N R54E
AP 4 | AP 3
TR 38 | TR 37
S 5 | AP 2
T39N | TR 39
R54E |

1978

S. $89^{\circ} 56'$ E., along line 3-4, Tract No. 37 and line 2-1, Tract No. 39.

- 13.00 Gance Creek, 15 lks. wide, 2 ft. deep, course SE.
- 20.05 Point for Angle Point No. 4, Tract No. 37, identical with Angle Point No. 1, Tract No. 39, Angle Point No. 2, Tract No. 40 and the C $\frac{1}{4}$ sec. cor. of sec. 5, as surveyed by U. S. Deputy Surveyor, H. B. Maxson.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

| T39N
AP 4 | R54E
TR 37 | S 5
AP 1 | AP 2
TR 39 | TR 40

1978