

507

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,  
THROUGH A PORTION OF R. 54 E., MDM, NEVADA

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

SC  
T41N R54E  
S 32 | S 33

1963

bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Corner is located at cor. of fence, bearing E. and N.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 40 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
U. S. Deputy Surveyors A. J. Hatch and J. H. Eaton,  
in 1870.

The cor. of Tps. 39 and 40 N., Rs. 54 and 55 E., monumented with a wooden post, 1 in. square, broken in pieces, with illegible scribe marks visible and loosely set in a mound of earth.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T40N  
R54E R55E  
S 36 | S 31  
S 1 | S 6  
T39N

1966

bury the original wooden post alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.

N. 89° 25' W., bet. secs. 1 and 36.

Over rolling land, through medium undergrowth.

33.10 Trail road, bears NW. and SE.

39.95 The ¼ sec. cor. of secs. 1 and 36, determined at the cor. of fence, bearing S. and W., this point is accepted as the best available evidence of the position of the original corner.

At the corner point