

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
T. 40 N., R. 55 E.

CHAINS

N. 0° 15' E., beginning new measurement.

Asc. 140 ft. over a rolling S. slope.

21.00 Wash, 10 lks. wide, 3 ft. deep, drains SSE.

22.20 Trail road, bears SE. and NW.

38.10 Intersect the Eighth Standard Parallel North.

The closing corner of secs. 3 and 4, T. 40 N., R. 55 E., monumented with a basalt stone, 16x10x8 ins., mkd. with 3 notches on the E. and W. edges and CC on the S. face, firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone to top, 5 ft. base, with brass cap mkd.

T41N R55E
S 34
S 4 | S 3
T40N R55E
C C

1963

reset the marked stone alongside the iron post.

From this corner, the standard cor. of secs. 33 and 34, T. 41 N., R. 55 E., bears WEST, 0.10 chs. dist., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.

From this same corner, the standard ¼ sec. cor. of sec. 34, T. 41 N., R. 55 E., bears EAST, 39.73 chs. dist., monumented with a basalt stone, 16x10x8 ins., mkd. SC ¼ on the N. face and firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone to top, 5 ft. base, with brass cap mkd.

S C
T41N R55E
¼ S 34

1963

reset the marked stone alongside the iron post.

Land, rolling.

Soil, clay and rocky.

Undergrowth, sagebrush and bunchgrass.