

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
T. 40 N., R. 55 E.

CHAINS

38.42

Intersect the Eighth Standard Parallel North.

The closing corner of secs. 4 and 5, T. 40 N., R. 55 E., monumented with a basalt stone, 30x12x8 ins., mkd. with 2 notches on the W. edge, 4 notches on the E. edge and CC on the S. face, firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to top, 5 ft. base, with brass cap mkd.

T41N	R55E
S 33	
S 5	S 4
T40N	R55E
C C	

1963

reset the marked stone alongside the iron post.

From this corner, the standard cor. of secs. 32 and 33, T. 41 N., R. 55 E., bears N. 89° 52' W., 1.42 chs. dist., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.

From this same corner, the standard ¼ sec. cor. of sec. 33, T. 41 N., R. 55 E., bears S. 89° 52' E., 38.48 chs. dist., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.

Land, rolling and broken.

Soil, clay and rocky.

Undergrowth, sagebrush and bunchgrass.

The point for the N. ¼ sec. cor. of sec. 4 is on the Eighth Standard Parallel North and at proportionate distance on the N. bdy. of sec. 4.

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to top, 5 ft. base, with brass cap mkd.

¼ S 4	
T40N R55E	

1963

From this corner, the standard ¼ sec. cor. of sec. 33, T. 41 N., R. 55 E., bears N. 89° 58' W., 1.62 chs. dist., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.