

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES OF T. 41 N., R. 55 E.

CHAINS

reset the marked stone alongside the iron post.

N. 0° 31' W., beginning new measurement.

Asc. 20 ft. along a W. slope.

2.00 Small spur, slopes SW.; desc. 20 ft. over a NW. slope.

5.10 Small wash, drains SW.; asc. 170 ft. over a SW. slope.

21.00 Ridge, bears NE. and SW.; desc. 70 ft. over a NW. slope.

35.37 The closing corner of secs. 4 and 5, T. 41 N., R. 55 E., monumented with a conglomerate stone, 12x10x6 ins., mkd. with 4 notches on the E. edge, 2 notches on the W. edge and CC on S. face, firmly set in the ground.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T42N R55E
S 32
S 5 | S 4
CC
T41N

1963

bury the marked stone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.

From this corner, the cor. of secs. 32 and 33, T. 42 N., R. 55 E., hereinbefore described, bears N. 89° 50' E., 0.65 chs. dist.

From the same corner, the ¼ sec. cor. of sec. 32, hereinbefore described, bears S. 89° 50' W., 38.99 chs. dist.

Land, rolling hills.

Soil, clay loam and gravel.

Undergrowth, sagebrush and bunchgrass.

The point for the N. ¼ sec. cor. of sec. 5, on the S. bdy. of sec. 32, T. 42 N., R. 55 E., is at proportionate distance based upon the original plat.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T42N R55E
¼ S 5
T41N R55E

1963