

## CHAINS

T40N	R60E
S 32	S 33
S 5	S 4
T39N	
1962	

Bury the original corner alongside of the iron post.

Land, rolling.

Soil, clay loam.

Undergrowth, sagebrush and greasewood.

N. 89° 21' W., bet. secs. 5 and 32.

Over rolling desert land.

34.40 Bladed road, bears NW. and SE.

40.91 Point for the  $\frac{1}{4}$  sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T40N	R60E
$\frac{1}{4}$ S 32	
S 5	S 5
T39N	
1962	

78.90 Trail road, bears N. and S.

79.90 Wire fence, bears N. and S.

81.82 Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.

T40N	R60E
S 31	S 32
S 6	S 5
T39N	
1962	

Land, rolling.

Soil, clay loam.

Undergrowth, sagebrush and greasewood.

N. 89° 21' W., bet. secs. 6 and 31.

Over rolling desert land.

6.10 Bladed road, bears N. and S., enter meadow.

40.91 Point for the  $\frac{1}{4}$  sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap mkd.