

DEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL SOUTH,
THROUGH RANGE 50 EAST

CHAINS 12.44	The closing cor. of secs. 1 and 2, T. 17 S., R. 50 E., hereinafter described.												
26.70	Wash, 30 lks. wide, 3 ft. deep, drains S.												
39.80	Track road, bears NE. and SW.												
40.47	Point for the standard $\frac{1}{4}$ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr><td>S</td><td>C</td></tr> <tr><td>T16S</td><td>R50E</td></tr> <tr><td>$\frac{1}{4}$ S</td><td>36</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">1963</td></tr> </table> </div>	S	C	T16S	R50E	$\frac{1}{4}$ S	36	<hr/>		1963			
S	C												
T16S	R50E												
$\frac{1}{4}$ S	36												
<hr/>													
1963													
	raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of cor. Continue over slightly rolling land, through heavy undergrowth.												
52.86	The $\frac{1}{4}$ sec. cor. of sec. 1, T. 17 S., R. 50 E., hereinafter described.												
80.95	Point for the standard cor. of Tps. 16 S., Rs. 50 and 51 E., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr><td>S</td><td>C</td></tr> <tr><td>T 16 S</td><td></td></tr> <tr><td>R50E</td><td>R51E</td></tr> <tr><td><u>S 36</u></td><td><u>S 31</u></td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">1963</td></tr> </table> </div>	S	C	T 16 S		R50E	R51E	<u>S 36</u>	<u>S 31</u>	<hr/>		1963	
S	C												
T 16 S													
R50E	R51E												
<u>S 36</u>	<u>S 31</u>												
<hr/>													
1963													
	raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of cor. From this stan. cor. the Fourth Stan. Par. was retraced eastward to establish the latitudinal control for the closing cor. of Tps. 17 S., Rs. 50 and 51 E., hereinafter described. Corners were thoroughly searched for along this line and the first one recovered was the original stan. township cor. of Tps. 16 S., Rs. 51 and 52 E. This cor. bears N. $89^{\circ} 46'$ E., 485.69 chs. dist. and was monumented with a squared wooden post, 3 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr><td>S</td><td>C</td></tr> <tr><td>T 16 S</td><td></td></tr> <tr><td>R51E</td><td>R52E</td></tr> <tr><td><u>S 36</u></td><td><u>S 31</u></td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">1963</td></tr> </table> </div>	S	C	T 16 S		R51E	R52E	<u>S 36</u>	<u>S 31</u>	<hr/>		1963	
S	C												
T 16 S													
R51E	R52E												
<u>S 36</u>	<u>S 31</u>												
<hr/>													
1963													
	Land, slightly rolling. Soil, sandy and gravelly clay loam. Timber, none; undergrowth, creosote bush and shadscale.												
	Dependent Resurvey, E. Bdy., T. 17 S., R. 50 E.												