

## DEPENDENT RESURVEY, PORTION OF W. BDY., T. 17 S., R. 50 E.

## CHAINS

N. 1° 29' W., bet. secs. 7 and 12.

Over gently rolling land, through scattering undergrowth.

4.00 Road, unimproved, bears NW. and SE.

38.81 The  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, monumented with a basalt stone, 10x10x8 ins., firmly set in the ground, marked and witnessed as described in the official record.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S  
R49E R50E  
 $\frac{1}{4}$   
S 12 | S 7  
1963

raise a mound of stone, 3 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. and reset the original cornerstone alongside the iron post.

N. 1° 32' W., beginning new measurement.

Over nearly level land, through scattering undergrowth.

38.74 The cor. of secs. 1, 6, 7 and 12, monumented with a basalt stone, 18x10x8 ins., firmly set in the ground, marked and witnessed as described in the official record.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S  
R49E R50E  
S 1 | S 6  
S 12 | S 7  
1963

raise a mound of stone, 3 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. and reset the original cornerstone alongside the iron post.

Land, gently rolling to nearly level.

Soil, sandy and gravelly clay loam.

Timber, none; undergrowth, sagebrush and creosote bush.

N. 1° 31' W., bet. secs. 1 and 6.

Over nearly level land, through scattering undergrowth.

39.67 Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.