

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 17 S., R. 50 E.

CHAINS

38.03 Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T17S R50E
1/4
S 3 | S 2
1963

deposit broken glass around the iron post, 6 ins. below the surface of the ground.

Continue over gently rolling land, through scattering undergrowth.

74.30 Intersect the Fourth Standard Parallel South.

Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T16S R50E
S 35
S 3 | S 2
T17S R50E
CC
1963

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the standard cor. of secs. 34 and 35, T. 16 S., R. 50 E., hereinbefore described, bears S. 89° 46' W., 12.48 chs. dist.

Land, gently rolling.
Soil, sandy and gravelly clay loam.
Timber, none; undergrowth, sagebrush and creosote bush.

The point for the N. 1/4 sec. cor. of sec. 2 is at mid-point and on the N. bdy. of the Tp.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T16S R50E
1/4 S 2
T17S R50E
1963

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the standard 1/4 sec. cor. of sec. 35, T. 16 S., R. 50 E., hereinbefore described, bears S. 89° 46' W., 12.46 chs. dist.