

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 17 S., R. 50 E.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17S R50E
 $\frac{1}{4}$
 S 4 | S 3
 1963

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Continue over gently rolling land, through scattering undergrowth.

71.60

Intersect the Fourth Standard Parallel South.

Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T16S R50E
 S 34
 S 4 | S 3
 T17S R50E
 CC
 1963

raise a mound of stone, 3½ ft. base, 2 ft. high, S. of cor. and deposit broken glass around the iron post, 6 ins. below the surface of the ground.

From this cor. the standard cor. of secs. 33 and 34, T. 16 S., R. 50 E., hereinbefore described, bears S. 89° 46' W., 12.66 chs. dist.

Land, gently rolling.
 Soil, sandy and gravelly clay loam.
 Timber, none; undergrowth, sagebrush and creosote bush.

The point for the N. ¼ sec. cor. of sec. 3 is at midpoint and on the N. bdy. of the Tp.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T16N R50E
 $\frac{1}{4}$ S 3
 T17S R50E
 1963

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. and deposit broken glass around the iron post, 6 ins. below the surface of the ground.

From this corner, the standard ¼ sec. cor. of sec. 34, T. 16 S., R. 50 E., hereinbefore described, bears S. 89° 46' W., 12.57 chs. dist.