

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 17 S., R. 50 E.

CHAINS	
79.50	Pole line, bears N. and S.
79.89	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, none; undergrowth, sagebrush and creosote bush.</p>
31.50	<p>N. 5° 18' W., bet. secs. 4 and 5.</p> <p>Over nearly level land, through scattering undergrowth.</p> <p>Road, graded and bladed, bears WNW. and ESE.</p>
36.27	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 5 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T17S R50E $\frac{1}{4}$ S 5 S 4 1963</p>
71.68	<p>deposit broken glass around the iron post, 5 ins. below the surface of the ground.</p> <p>Continue over nearly level land, through medium heavy undergrowth.</p> <p>Intersect the Fourth Standard Parallel South.</p> <p>Point for the closing corner of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;">T16S R50E S 33 S 5 S 4 T17S R50E CG 1963</p> <p>deposit broken glass around the iron post, 6 ins. below the surface of the ground.</p> <p>From this cor. the standard cor. of secs. 32 and 33, T. 16 S., R. 50 E., hereinbefore described, bears S. 89° 46' W., 12.33 chs. dist.</p> <p>Land, nearly level. Soil, sandy and gravelly clay loam. Timber, none; undergrowth, sagebrush and creosote bush.</p> <p>The point for the N. $\frac{1}{4}$ sec. cor. of sec. 4 is at midpoint, and on the N. bdy. of the Tp.</p> <p>At the corner point</p>